

Nawiewnik kierunkowy AWK-D - dane techniczne

Zakres produkcji:

Wielkość	▣ A	Ø D	Ilość dysz Ø 38 mm	Ilość dysz Ø 55 mm	Typ nawiewnika
300	310	-	36	-	AWK-D-1-PK/310-36
			-	16	AWK-D-2-PK/310-16
	-	310	-	-	AWK-D-1A/310-25
			-	-	AWK-D-2A/310-12
			25	-	AWK-D-1-PO/310-25
			-	12	AWK-D-2-PO/310-12
400	398	-	64	-	AWK-D-1-PK/400-64
			-	24	AWK-D-2-PK/400-24
	-	398	-	-	AWK-D-1A/400-45
			-	-	AWK-D-2A/400-24
			45	-	AWK-D-1-PO/400-45
			-	24	AWK-D-2-PO/400-24
500	498	-	100	-	AWK-D-1-PK/500-100
			-	36	AWK-D-2-PK/500-36
	-	498	-	-	AWK-D-1A/500-79
			-	-	AWK-D-2A/500-36
			79	-	AWK-D-1-PO/500-79
			-	36	AWK-D-2-PO/500-36
600	595	-	144	-	AWK-D-1-PK/600-144
			-	48	AWK-D-2-PK/600-48
	-	595	-	-	AWK-D-1A/600-114
			-	-	AWK-D-2A/600-58
			114	-	AWK-D-1-PO/600-114
			-	58	AWK-D-2-PO/600-58

Kierunki wypływu w zależności od ustawienia dysz:

